

Fast and
reliable

TDR 8 Manual

The Turbo Deli Rotisserie is the fastest original rotisserie in the industry. The TDR's cavity is fed with fresh air, cooking a rotisserie chicken as it is meant to be: crispy and delicious while maintaining an attractive appearance for hours.

The TDR pushes the air throughout the cavity, resulting in an improved heat transfer on the products. It consumes less electricity during the preparation process. Add to this the improved cooking time and you have the most energy efficient rotisserie and a high output.

The double glass doors create a striking, large display section that maximises your products' visual appeal to customers! It also offers perfect insulation with contact temperatures below 70°C.



Features TDR 8 Manual

Top features

- Controls with manual settings
- Easy to operate - set time, temperature and start the rotisserie
- Endless possibilities: poultry (parts), pork roast, ribs, lamb, roast beef, pork belly, meat loaf, porchetta and other proteins

Standard characteristics

- 8 Meat fork, V-spit, basket or rack positions
- Rotor for up to 40 chickens (1,2 kg)
- Range of accessories available for preparation of chicken, chicken parts, ribs, etc.

Accessories

- Door handle set on customer side for pass through operation
- Meat forks (included)
- Multi-purpose baskets
- V-spits
- Chicken racks
- Matching stand on castors

Optional


- Stacked unit
- Pass-through
- Ventless hood



Manual controls



Rotor button on customer side



Ventless hood (optional)



Stacked TDR

TDR 8 Manual

- 1 Power cable 2.2 m
- 2 Exhaust opening
- 3 Space to the wall
- 4 Location for socket

Dimensions TDR 8

Width	1005 mm
Depth	830 mm
Depth with hood	970 mm
Height	1065 mm
Height on stand	1796 mm
Height with hood	1395 mm

Technical data TDR 8

Net weight	185 kg
Gross weight	216 kg
Voltage	3N~ 400/230 V
Frequency	50/60 Hz
Power	10.5 kW

Dimensions TDR 8+8

Width	1005 mm
Depth	830 mm
Depth with hood	970 mm
Height	2095 mm
Height with hood	2344 mm

Technical data TDR 8+8

Net weight	375 kg
Gross weight	435 kg
Voltage	3N~ 400/230 V
Frequency	50/60 Hz
Power	21 kW

Specifications and technical data are subject to amendment without prior notice.

These are basic drawings. For more detailed technical information, please refer to the installation manual at www.frijado.com.

